

### 3SF1324-1SE21-1BA1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3sf1324-1se21-1ba1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.45 kgs
<b>Customs Tariff Code</b>	85365019
<b>EAN</b>	4011209720275.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	3758
<b>UPC</b>	754554952222.0
<b>Product ID</b>	3SF1324-1SE21-1BA1
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.03.2017
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	N
<b>eClass 6</b>	27-27-06-11
<b>eClass 7.1</b>	27-27-06-11
<b>eClass 8</b>	27-27-06-11
<b>eClass Version 9</b>	27-27-06-11
<b>eClass Version 9.1</b>	27-27-06-11
<b>ETIM 7</b>	EC002593
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Packaging Length</b>	251,50
<b>Packaging Width</b>	151,00
<b>Packaging Height</b>	68,50
<b>Packaging Size</b>	MM
<b>Product Description</b>	WYŁĄCZNIK POZYCYJNY Z RYGLEM I ASISAFE, , SIŁA ZAMYKANIA 1500N, , OBUDOWA Z TWORZYWA, WTYCZKA M12, 4-BIEG., KANAŁ1=EL. URUCH. 1NC, KANAŁ2=MAGNES 1NC , BLOKADA SPRĘŻYNOWA, ODBLOKOWANIE PRZEZ MECH. Z ZAMKIEM, NAPIĘCIE MAGNESU 24 V DC/AC, NADZÓR EL. URUCH. 2
<b>Comparative Metals Coefficient</b>	01.03.2017
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368
<b>Unit of Measure</b>	ST

## Description

Safety position switch with tumbler Locking force 1300 N 5 directions of approaches  
Plastic enclosure, M12 connector ASIsafe integrated Channel 1=actuator 1 NC Channel  
2=magnet 1 NC spring-locked Auxiliary release lock on front Magnet voltage 24 V DC/AC  
Monitoring actuator 2 NC/1 NO Monitoring magnet 2 NC/1 NO The matching separate Actuator  
3SE5000-0AV0 must be ordered separately