

3SF1324-1SF21-1BA1

Industrial automation components

Manufacturer	Siemens
Catalog number	3sf1324-1sf21-1ba1
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.91 kgs
Product Description	WYŁĄCZNIK POZYCYJNY Z RYGLEM I ASISAFE, , SIŁA ZAMYKANIA 1500N, , OBUDOWA Z TWORZYWA, WTYCZKA M12, 4-BIEG., KANAŁ1=EL. URUCH. 1NC, KANAŁ2=MAGNES 1NC , BLOKADA SPRĘŻYNOWA, ODBLOKOWANIE EWAKUACYJNE OD PRZODU, NAPIĘCIE MAGNESU 24 V DC/AC, NADZÓR EL. URUCH. 2
Comparative Metals Coefficient	01.03.2017
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368
Unit of Measure	ST
Customs Tariff Code	85365019
EAN	4011209740877.0
Quantity in Package	1
Product Code	3758
Product ID	3SF1324-1SF21-1BA1
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.03.2017
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-27-06-11
eClass 7.1	27-27-06-11
eClass 8	27-27-06-11
eClass Version 9	27-27-06-11
eClass Version 9.1	27-27-06-11
ETIM 7	EC002593
Group Classification Key	R711
List of Characteristics	CC-IC10
Packaging Length	251,50
Packaging Width	151,00
Packaging Height	68,50
Packaging Size	MM

Description

Safety position switch with tumbler Locking force 1300 N 5 directions of approaches Plastic enclosure, M12 connector ASISafe integrated Channel 1=actuator 1 NC Channel 2=magnet 1 NC spring-locked Escape release on the front Magnet voltage 24 V DC/AC Monitoring actuator 2 NC/1 NO Monitoring magnet 2 NC/1 NO The matching separate Actuator 3SE5000-0AV0 must be ordered separately