

3SK1111-1AB30

Industrial automation components

Manufacturer	Siemens
Catalog number	3sk1111-1ab30
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.12 kgs
Customs Tariff Code	85371098
Quantity in Package	1
Product Code	3761
EAN	4011209913509.0
Product ID	3SK1111-1AB30
AL Field	N
Compliance	Produkt zgodny z RoHS od: 05.11.2012
Configurable Product	False
eClass Version 9.1	27-37-18-19
ETIM 7	EC001449
Group Classification Key	R711
List of Characteristics	CC-IC10
Country of Origin	DE
ECCN	N
eClass 6	27-37-18-19
eClass 7.1	27-37-18-19
eClass 8	27-37-18-19
eClass Version 9	27-37-18-19
Packaging Length	109,00
Packaging Width	36,00
Packaging Height	152,00
Packaging Size	MM
Product Description	PRZEKAŹNIK BEZPIECZEŃSTWA SIRIUS, WERSJA STANDARD, WYJŚCIA PRZEKAŹNIKOWE: 3 STYKI NO + WYJŚCIA PRZEKAŹNIKOWE SYGNALIZACYJNE: 1 STYK NC, NAPIĘCIE ZASILANIA = 24 V AC/DC ZACISKI ŚRUBOWE
Comparative Metals Coefficient	05.11.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST

Description

3SK1111-1AB30 | Siemens, 3SK1 Series, Safety Relay, 24 V ac/dc, 1 Channel, 1NC/3NO, 2 Contacts, 22.5 X 100 X 121.6 mm | Brand / Manufacturer: Siemens | product type: Safety Relay | series: 3SK1 | supply voltage: 24 V ac/dc | number of channels: 1 | function: Sensor Floating;Sensor Non-Floating;Monitored Start;Autostart | auxiliary contacts: 1NC/3NO | protection class ISO 13849 1: 4 | requirements met: CCC;CSA;UL;EAC;C-Tick;CE;LRS;RINA;RMRS | security contacts: 2 | voltage on terminals: Screw | type of attachment: Screw Mount;Snap On Mount | Size: 22.5 x 100 x 121.6 mm | operating temperature range: -25 to +60 °C