

### 3SK1111-2AW20

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3sk1111-2aw20
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.45 kgs
<b>Quantity in Package</b>	1
<b>Product Code</b>	3761
<b>Customs Tariff Code</b>	85371098
<b>EAN</b>	4011209913530.0
<b>Product ID</b>	3SK1111-2AW20
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-18-19
<b>eClass 7.1</b>	27-37-18-19
<b>eClass 8</b>	27-37-18-19
<b>eClass Version 9</b>	27-37-18-19
<b>eClass Version 9.1</b>	27-37-18-19
<b>ETIM 7</b>	EC001449
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Packaging Length</b>	109,00
<b>Packaging Width</b>	36,00
<b>Packaging Height</b>	152,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	PRZEKAŹNIK BEZPIECZEŃSTWA SIRIUS, WERSJA STANDARD, WYJŚCIA PRZEKAŹNIKOWE: 3 STYKI NO + WYJŚCIA PRZEKAŹNIKOWE SYGNALIZACYJNE: 1 STYK NC, NAPIĘCIE ZASILANIA = 110 - 230 V AC 50/60 HZ ZACISKI SPRĘŻYNOWE
<b>Comparative Metals Coefficient</b>	05.11.2012
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
<b>Unit of Measure</b>	ST
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 05.11.2012
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE

## Description

3SK1111-2AW20 | Siemens, SIRIUS Series, Safety Relay, 110 to 240 V ac/dc, 1NC/3NO, Spring Loaded Terminal, 22.5 x 121.6 x 100 mm | Brand / Manufacturer: Siemens | product type: Safety Relay | series: SIRIUS | supply voltage: 110 to 240 V ac/dc | number of channels: 3 | auxiliary contacts: 1NC;3NO | protection class ISO 13849 1: 4 | requirements met: CCC Certified;CSA Certified;UL Listed;EAC Certified;C-Tick Marked;CE Certified | security contacts: 3 | voltage on terminals: Spring Loaded