

### 3SU1002-2BC10-0AA0

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3su1002-2bc10-0aa0               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |  |
|--------------------------------|--|
| Packaging Length               | 40,00  |
| Packaging Width                | 20,00  |
| Packaging Height               | 20,00  |
| Packaging Size                 | MM   |
| Product Description            | Przełącznik obrotowy podświetlany, 22 mm, okrągły, tworzywo sztuczne, czarny, Pióro krótkie, 2 położenia przełączania 0<I, impulsowy, kąt załączenia 45°, 10:30h/12h |
| Comparative Metals Coefficient | 01.10.2014   |
| Unit of Measure                | ST   |
| Product ID                     | 3SU1002-2BC10-0AA0   |
| Compliance                     | Produkt zgodny z RoHS od: 01.10.2014   |
| Configurable Product           | False  |
| Country of Origin              | CZ   |
| ECCN                           | N  |
| eClass 6                       | 27-37-12-13  |
| eClass 7.1                     | 27-37-12-13  |
| eClass 8                       | 27-37-12-13  |
| eClass Version 9               | 27-37-12-13  |
| eClass Version 9.1             | 27-37-12-13  |
| ETIM 7                         | EC000222   |
| Group Classification Key       | R711   |
| List of Characteristics        | CC-IC10  |
| Customs Tariff Code            | 85389099   |
| EAN                            | 4047621016511.0  |
| Quantity in Package            | 1  |
| AL Field                       | N  |
| Product Code                   | 5452   |
| UPC                            | 804766474439.0   |
| Weight                         | 20   |