

3SU1100-2BM60-3NA0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3su1100-2bm60-3na0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| eClass Version 9.1 | 27-37-12-43 |
| ETIM 7 | EC001029 |
| Group Classification Key | R711 |
| Metals Coefficient | LA0----- |
| Packaging Length | 130,00 |
| Packaging Width | 70,00 |
| Packaging Height | 30,00 |
| Packaging Size | MM |
| Comparative Metals Coefficient | 01.10.2014 |
| Product ID | 3SU1100-2BM60-3NA0 |
| Compliance | Produkt zgodny z RoHS od: 01.10.2014 |
| Country of Origin | DE |
| ECCN | N |
| eClass 6 | 27-37-12-43 |
| eClass 7.1 | 27-37-12-43 |
| eClass 8 | 27-37-12-43 |
| eClass Version 9 | 27-37-12-43 |
| Product Description | Przełącznik obrotowy, podświetlany, 22 mm, okrągły, tworzywo sztuczne, biały, Pióro, krótki, 3 położenia przełączania I>0<II, impulsowy, 10:30h/12h/13:30h, z uchwytem, 1N0, 1N0, przyłącze sprężynowe |
| Unit of Measure | ST |
| Product Code | 5452 |
| UPC | 804766070488.0 |
| Weight | 64 |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85365080 |
| Copper Weight | 0 |
| EAN | 4011209957657.0 |
| Quantity in Package | 1 |
| AL Field | N |
| Configurable Product | False |
| List of Characteristics | CC-IC10 |