

### 3TC4417-0AF4

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3tc4417-0af4
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.47 kgs
<b>Product ID</b>	3TC4417-0AF4
<b>AL Field</b>	N
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85364900
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.02.2012
<b>Configurable Product</b>	False
<b>Copper Weight</b>	0
<b>Country of Origin</b>	DE
<b>EAN</b>	4011209034433.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-10-18
<b>eClass 7.1</b>	27-37-10-18
<b>eClass 8</b>	27-37-10-18
<b>eClass Version 9</b>	27-37-10-18
<b>eClass Version 9.1</b>	27-37-10-18
<b>ETIM 7</b>	EC002552
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Metals Coefficient</b>	LDP-----
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	96,00
<b>Packaging Width</b>	80,00
<b>Packaging Height</b>	153,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	STYCZNIK WLK. 2 2-P, DC-3 I 5, 32 A, ŁĄCZNIK POMOC. 22 (2N0+2NC), ZASIL. DC, DC 110 V
<b>Product Code</b>	5807
<b>Comparative Metals Coefficient</b>	01.02.2012
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; lblREACHCode0237 lblREACHCasNo0237
<b>Unit of Measure</b>	ST
<b>UPC</b>	754554185019.0