

### 3TX7402-3A

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3tx7402-3a
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.01 kgs
<b>Unit of Measure</b>	ST
<b>UPC</b>	754554203843.0
<b>Product ID</b>	3TX7402-3A
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85363010
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.03.2017
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>EAN</b>	4011209055384.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-10-13
<b>eClass 7.1</b>	27-37-10-13
<b>eClass 8</b>	27-37-10-13
<b>eClass Version 9</b>	27-37-10-13
<b>eClass Version 9.1</b>	27-37-10-13
<b>ETIM 7</b>	EC000197
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	34,00
<b>Packaging Width</b>	27,00
<b>Packaging Height</b>	15,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	Bezpiecznik przepięciowy Dioda przeciwzakłóceńowa z uchwytem dystansowym przewodów DC 24-250 V do montażu w zacisku cewki do styczników pomocniczych 3TH4
<b>Product Code</b>	5803
<b>Comparative Metals Coefficient</b>	01.03.2017