

### 3UF7000-1AB00-0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3uf7000-1ab00-0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.14 kgs
<b>Product ID</b>	3UF7000-1AB00-0
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85364900
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.05.2012
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>EAN</b>	4011209593817.0
<b>ECCN</b>	EAR99
<b>eClass 6</b>	27-37-08-04
<b>eClass 7.1</b>	27-37-08-04
<b>eClass 8</b>	27-37-08-04
<b>eClass Version 9</b>	27-37-08-04
<b>eClass Version 9.1</b>	27-37-08-04
<b>ETIM 7</b>	EC002572
<b>Group Classification Key</b>	R711
<b>List of Characteristics</b>	CC-IC10
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	115,50
<b>Packaging Width</b>	53,00
<b>Packaging Height</b>	125,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	JEDNOSTKA PODSTAWOWA 1 SIMOCODE PRO C, ZŁĄCZE PROFIBUS DP 12 MBIT/S, RS485, 4WE/3WY DOWOLNIE PROGRAMOWALNE, OCHRONA TERMISTOROWA, WYJŚCIA PRZEKAŹNIKOWE MONOSTABILNE, US: DC 24V
<b>Product Code</b>	5836
<b>Comparative Metals Coefficient</b>	01.05.2012
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368
<b>Unit of Measure</b>	ST
<b>UPC</b>	754554901640.0