

### 3UF73201AU000

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3uf73201au000                    |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Legacy / discontinued            |

## Technical specification

|                                |                                                                                                                                                           |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight                         | 0.18 kgs                                                                                                                                                  |
| Product ID                     | 3UF7320-1AU00-0                                                                                                                                           |
| AL Field                       | N                                                                                                                                                         |
| Customs Tariff Code            | 85371098                                                                                                                                                  |
| Compliance                     | Produkt zgodny z RoHS od: 01.05.2012                                                                                                                      |
| Configurable Product           | False                                                                                                                                                     |
| Country of Origin              | DE                                                                                                                                                        |
| EAN                            | 4011209841789.0                                                                                                                                           |
| ECCN                           | N                                                                                                                                                         |
| eClass 6                       | 27-37-08-05                                                                                                                                               |
| eClass 7.1                     | 27-37-08-05                                                                                                                                               |
| eClass 8                       | 27-37-08-05                                                                                                                                               |
| eClass Version 9               | 27-37-08-05                                                                                                                                               |
| eClass Version 9.1             | 27-37-08-05                                                                                                                                               |
| ETIM 7                         | EC002613                                                                                                                                                  |
| Group Classification Key       | R711                                                                                                                                                      |
| List of Characteristics        | CC-IC10                                                                                                                                                   |
| Quantity in Package            | 1                                                                                                                                                         |
| Packaging Length               | 133,00                                                                                                                                                    |
| Packaging Width                | 52,50                                                                                                                                                     |
| Packaging Height               | 133,00                                                                                                                                                    |
| Packaging Size                 | MM                                                                                                                                                        |
| Product Code                   | 5836                                                                                                                                                      |
| Comparative Metals Coefficient | 01.05.2012                                                                                                                                                |
| REACH                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830 |
| Unit of Measure                | ST                                                                                                                                                        |
| UPC                            | 40892789850.0                                                                                                                                             |

## Description

Fail-safe digital module DM-F local, for fail-safe shutdown via hardware signal Us: 110...240 V AC/DC 2 relay enabling circuits, 2 relay outputs, safety function can be set via DIP switch, maximum achievable SIL IEC 61508: 3, maximum achievable PL ISO 13849-1: E