

### 3UF7330-1AB00-0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3uf7330-1ab00-0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	3UF7330-1AB00-0
AL Field	N
Customs Tariff Code	85371098
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Country of Origin	DE
EAN	4011209841772.0
ECCN	N
eClass 6	27-37-08-05
eClass 7.1	27-37-08-05
eClass 8	27-37-08-05
eClass Version 9	27-37-08-05
eClass Version 9.1	27-37-08-05
ETIM 7	EC002613
Group Classification Key	R711
List of Characteristics	CC-IC10
Quantity in Package	1
Packaging Length	133,00
Packaging Width	52,50
Packaging Height	133,00
Packaging Size	MM
Product Description	MODUŁ CYFORWY SAFETY PROFISAFE, DO REALIZACJI BEZPIECZNEGO WYŁĄCZENIA POPRZEZ MAGISTRALĘ PROFISAFE; NAPIĘCIE.ZASIL.:24V DC, 2 WYJSCIA ZWALNIAJACE, 2 WYJŚCIA PRZEKAŹNIKOWE, 3 WEJŚCIA; NAJWYŻSZY MOŻLIWY DO UZYSKANIA POZIOM BEZPIECZEŃSTWA WG KAT. SIL (IEC 61
Product Code	5836
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Lead titanium zirconium oxide lblREACHCasNo0830
Unit of Measure	ST
UPC	40892789874.0
Weight	362

## Description

Fail-safe digital module DM-F PROFIsafe, for fail-safe shutdown via bus/PROFIsafe, Us: 24 V DC, 2 relay enabling circuits, 2 relay outputs, 3 inputs, maximum achievable SIL IEC 61508: 3, maximum achievable PL ISO 13849-1: E