

### 3UG45012AW30

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 3ug45012aw30                     |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Legacy / discontinued            |

## Technical specification

|                                |   |
|--------------------------------|---|
| Product ID                     | 3UG4501-2AW30   |
| AL Field                       | N   |
| Aluminium Weight               | 0   |
| Argent Weight                  | 0   |
| Customs Tariff Code            | 85364900  |
| Compliance                     | Produkt zgodny z RoHS od: 01.05.2012  |
| Configurable Product           | False   |
| Copper Weight                  | 0   |
| Country of Origin              | CZ  |
| EAN                            | 4011209665323.0   |
| ECCN                           | N   |
| eClass 6                       | 27-37-18-13   |
| eClass 7.1                     | 27-37-18-13   |
| eClass 8                       | 27-37-18-13   |
| eClass Version 9               | 27-37-18-13   |
| eClass Version 9.1             | 27-37-18-13   |
| ETIM 7                         | EC001447  |
| Group Classification Key       | R711  |
| List of Characteristics        | CC-IC10   |
| Metals Coefficient             | LA0-----  |
| Quantity in Package            | 1   |
| Packaging Length               | 109,00  |
| Packaging Width                | 99,00   |
| Packaging Height               | 30,00   |
| Packaging Size                 | MM  |
| Product Description            | ANALOGOWY PRZEKAŹNIK KONTROLI POZIOMU CIECZY PRZEWODZĄCYCH , CZUŁOŚĆ: 2 DO 200 KOHM , KONTROLA 1 LUB 2-PUNKTOWA, Z LED ŻÓŁTĄ/ZIEŁONĄ, AC/DC 24 DO 240V DC I AC 50 DO 60 HZ, ZWŁOKA WYZW. 0.5 DO 10S, ZE STYKIEM 1C0, Z ZACISKAMI SPRĘŻ. , |
| Product Code                   | 5885  |
| Comparative Metals Coefficient | 01.05.2012  |
| REACH                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Dicyclohexyl phthalate (DCHP) CAS-Nr. 84-61-7   |
| Unit of Measure                | ST  |
| UPC                            | 804766053207.0  |
| Weight                         | 123   |

## Description

Analog monitoring relay Fill level monitoring Resistance monitoring from 2 to 200 kohm  
Overshoot and undershoot 24 to 240 V AC/DC 50 to 60 Hz DC and AC 2-step or 1-step control  
Tripping delay 0.5 to 10 s 1 change-over contact spring-type connection system