

3UG4622-2AW30

Industrial automation components

Manufacturer	Siemens
Catalog number	3ug4622-2aw30
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Argent Weight	0
Customs Tariff Code	85364900
Compliance	Produkt zgodny z RoHS od: 01.05.2012
Configurable Product	False
Copper Weight	0
Country of Origin	DE
EAN	4011209642652.0
ECCN	N
eClass 6	27-37-18-02
eClass 7.1	27-37-18-02
eClass 8	27-37-18-02
eClass Version 9	27-37-18-02
eClass Version 9.1	27-37-18-02
ETIM 7	EC001440
Group Classification Key	R711
List of Characteristics	CC-IC10
Metals Coefficient	LA0-----
Quantity in Package	1
Packaging Length	99,00
Packaging Width	29,00
Packaging Height	107,00
Packaging Size	MM
Product Description	CYFROWY PRZEKAŹNIK KONTROLI PRĄDU 1-FAZ., ZAKRES OD 0,05 DO 10 A, PRZEKROCZENIE GÓRNEJ I DOLNEJ GRANICY, NAPIĘCIE STEROWNICZE 24 -240V AC/DC, OPÓŹNIENIE WYZWOLENIA 01-20s, HISTEREZA 0,01A-5A; STYKI 1C0; ZACISKI SPRĘŻYNOWE,
Product Code	5885
Comparative Metals Coefficient	01.05.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Dicyclohexyl phthalate (DCHP) CAS-Nr. 84-61-7
Unit of Measure	ST
UPC	40892948943.0
Weight	145
Product ID	3UG4622-2AW30
AL Field	N
Aluminium Weight	0

Description

3UG4622-2AW30 | Siemens Digital Monitoring Relay 1NO 240 V ac/dc Monitor for Current | Brand / Manufacturer: Siemens | height: 22.5 | width: 91 | depth: 96 | product type: Digital Monitoring Relay | type of relay: Monitoring Relay | contact configuration: 1NO | supply voltage: 240 V ac/dc | monitoring application: Current | number of bars: 1 | Minimum measurable current: 0.05 A | maximum measurable current: 15 A | time delay: 20 s | type of attachment: Snap-On Mount