

### 3VA1220-5EF32-0AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3va1220-5ef32-0aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	1.81 kgs
<b>Product ID</b>	3VA1220-5EF32-0AA0
<b>AL Field</b>	N
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85362090
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.06.2012
<b>Configurable Product</b>	False
<b>Copper Weight</b>	0
<b>Country of Origin</b>	CZ
<b>EAN</b>	4042948809396.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-04-09
<b>eClass 7.1</b>	27-37-04-09
<b>eClass 8</b>	27-37-04-09
<b>eClass Version 9</b>	27-37-04-09
<b>eClass Version 9.1</b>	27-37-04-09
<b>ETIM 7</b>	EC000228
<b>Group Classification Key</b>	P360
<b>List of Characteristics</b>	LV10.1
<b>Metals Coefficient</b>	L0A-----
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	175,00
<b>Packaging Width</b>	125,00
<b>Packaging Height</b>	123,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	wyłącznik 3VA1 IEC Frame 250 zdolność załączania M Icu=55kA przy 415V 3-bieg., ochrona instalacji TM240, ATAM, In=200A, zabezpieczenie od przeciążeń Ir=140A...200A zabezpieczenie przeciwzwarciove Ii=5...10 x In przyłącze płaskie śrubowe
<b>Product Code</b>	5375
<b>Comparative Metals Coefficient</b>	01.06.2012
<b>Unit of Measure</b>	ST
<b>UPC</b>	804766421631.0
<b>Article Number</b>	3VA12205EF320AA0
<b>Product Family</b>	Ordering Data Overview

<b>Catalog ID</b>	LV10.1
<b>Packaging Dimensions</b>	4.921 x 6.89 x 4.843
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	690 V, 415 V
<b>Product Group</b>	5375
<b>Net Weight</b>	3.505 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85362090
<b>Current Rating</b>	200 A
<b>Number of Poles</b>	3