

### 3VA20636HL420AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3va20636hl420aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

Product ID	3VA2063-6HL42-0AA0
AL Field	N
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362010
Compliance	Produkt zgodny z RoHS od: 01.06.2012
Configurable Product	False
UPC	804766447082.0
Weight	2740
Copper Weight	0
Country of Origin	CZ
EAN	4042948833506.0
ECCN	9N9999
eClass 6	27-37-04-09
eClass 7.1	27-37-04-09
eClass 8	27-37-04-09
eClass Version 9	27-37-04-09
eClass Version 9.1	27-37-04-09
ETIM 7	EC000228
Group Classification Key	P360
List of Characteristics	LV10.1
Metals Coefficient	LOA-----
Quantity in Package	1
Packaging Length	200,00
Packaging Width	169,00
Packaging Height	145,00
Packaging Size	MM
Product Code	5374
Comparative Metals Coefficient	01.06.2012
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420
Unit of Measure	ST
Article Number	3VA20636HL420AA0
Product Family	Ordering Data Overview
Catalog ID	LV10.1

<b>Packaging Dimensions</b>	6.654 x 7.874 x 5.709
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	690 V, 415 V
<b>Product Group</b>	5374
<b>Net Weight</b>	6.043 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85362010
<b>Current Rating</b>	63 A
<b>Number of Poles</b>	4

## Description

SIEMENS LOW VOLTAGE 3VA IEC MOLDED CASE CIRCUIT BREAKER WITH ELECTRONIC TRIP UNIT. 3VA20 FRAME WITH HIGH (CLASS H) BREAKING CAPACITY. 63A 4-POLE I<sub>cu</sub>: (2KAIC AT 690V) (85KAIC AT 415V). ETU320 TRIP UNIT LI. SPECIAL FEATURES: CONNECTION WITH LUG TERMINAL / NUT KEEPER. DIMENSIONS (W x H x D) IN: 5.5 x 7.1 x 4.2.