

3VA22255KP320AA0

Industrial automation components

Manufacturer	Siemens
Catalog number	3va22255kp320aa0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	3VA2225-5KP32-0AA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.06.2012
Configurable Product	False
Country of Origin	CZ
ECCN	9N9999
ETIM 7	EC000228
Group Classification Key	P360
List of Characteristics	LV10.1
Metals Coefficient	LOA-----
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362090
Copper Weight	0
EAN	4042948805473.0
eClass 6	27-37-04-09
eClass 7.1	27-37-04-09
eClass 8	27-37-04-09
eClass Version 9	27-37-04-09
eClass Version 9.1	27-37-04-09
Quantity in Package	1
Packaging Length	200,00
Packaging Width	134,00
Packaging Height	145,00
Product Code	5374
Comparative Metals Coefficient	01.06.2012
UPC	804766434396.0
Weight	2289
Article Number	3VA22255KP320AA0
Product Family	Ordering Data Overview
Catalog ID	LV10.1

Packaging Dimensions	5.276 x 7.874 x 5.709
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Voltage Rating	690 V, 415 V
Product Group	5374
Net Weight	5.053 lb
Packaging Quantity	1 pieces
Commodity Code	85362090
Current Rating	250 A
Number of Poles	3

Description

SIEMENS LOW VOLTAGE 3VA IEC MOLDED CASE CIRCUIT BREAKER WITH ELECTRONIC TRIP UNIT. 3VA22 FRAME WITH MEDIUM (CLASS M) BREAKING CAPACITY. 250A 3-POLE Icu: (3KAIC AT 690V) (55KAIC AT 415V). ETU850 TRIP UNIT LCD LSI WITH METERING. SPECIAL FEATURES: CONNECTION WITH LUG TERMINAL / NUT KEEPER. DIMENSIONS (W x H x D) IN: 4.1 x 7.1 x 4.2.