3VA22258HL320AA0

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Siemens
Catalog number	3va22258hl320aa0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	3VA2225-8HL32-0AA0
AL Field	N
Compliance	Produkt zgdony z RoHS od: 01.06.2012
Configurable Product	False
ECCN	9N9999
ETIM 7	EC000228
Group Classification Key	P360
List of Characteristics	LV10.1
Metals Coefficient	LOA-----
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Copper Weight	0
eClass 6	27-37-04-09

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.

eClass 7.1	27-37-04-09
eClass 8	27-37-04-09
eClass Version 9	27-37-04-09
eClass Version 9.1	27-37-04-09
Quantity in Package	1
Packaging Length	200,00
Packaging Width	134,00
Packaging Height	145,00
Part Number	5374
Comparative Metals Coefficient	01.06.2012
Product Description	wyłącznik 3VA2 IEC Frame 250 klasa zdolności łączeniowej L Icu=150kA przy 415V 3-bieg., ochrona instalacji ETU320, LI, In=250A zabezpieczenie od przeciążeń Ir=100A...250A zabezpieczenie przeciwzwarciowe Ii=1,5...10 x In przyłącze płaskie śrubowe
Product Family	Ordering Data Overview
Product Group	5374
Catalog ID	LV10.1
Net Weight	4.987 lb
Packaging Dimensions	5.276 x 7.874 x 5.709
Package Size Unit of Measure	Inch
Packaging Quantity	1 pieces
EAN	4042948832462
UPC	804766446054
Commodity Code	85362090
Number of Poles	3

Description

SIEMENS LOW VOLTAGE 3VA IEC MOLDED CASE CIRCUIT BREAKER WITH ELECTRONIC TRIP UNIT. 3VA22 FRAME WITH EXTREMELY HIGH (CLASS L) BREAKING CAPACITY. 250A 3-POLE Icu: (24KAIC AT 690V) (150KAIC AT 415V).

ETU320 TRIP UNIT LI. SPECIAL FEATURES: CONNECTION WITH LUG TERMINAL / NUT KEEPER. DIMENSIONS (W x H x D) IN: 4.1 x 7.1 x 4.2.