

### 3VA2325-6HL32-0AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3va2325-6hl32-0aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	3VA2325-6HL32-0AA0
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420
Unit of Measure	ST
UPC	804766446016.0
Weight	4703
AL Field	N
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362090
Compliance	Produkt zgodny z RoHS od: 01.04.2014
Configurable Product	False
Copper Weight	0
Country of Origin	CZ
EAN	4042948834343.0
ECCN	9N9999
eClass 6	27-37-04-09
eClass 7.1	27-37-04-09
eClass 8	27-37-04-09
eClass Version 9	27-37-04-09
eClass Version 9.1	27-37-04-09
ETIM 7	EC000228
Group Classification Key	P360
List of Characteristics	LV10.1
Metals Coefficient	LOA-----
Quantity in Package	1
Packaging Length	265,00
Packaging Width	165,00
Packaging Height	170,00
Packaging Size	MM
Product Description	wyłącznik 3VA2 IEC Frame 400 zdolność załączania H Icu=85kA przy 415V 3-bieg., ochrona instalacji ETU320, LI, In=250A zabezpieczenie od przeciążeń Ir=100A...250A zabezpieczenie przeciwzwarciowe Ii=1,5...12 x In przyłącze płaskie śrubowe
Product Code	5374
Comparative Metals Coefficient	01.04.2014

<b>Article Number</b>	3VA23256HL320AA0
<b>Product Family</b>	Ordering Data Overview
<b>Catalog ID</b>	LV10.1
<b>Packaging Dimensions</b>	6.496 x 10.433 x 6.693
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	690 V, 415 V
<b>Product Group</b>	5374
<b>Net Weight</b>	10.289 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85362090
<b>Current Rating</b>	250 A
<b>Number of Poles</b>	3