

3VA24405MN320AA0

Industrial automation components

Manufacturer	Siemens
Catalog number	3va24405mn320aa0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	3VA2440-5MN32-0AA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.06.2012
Configurable Product	False
Country of Origin	Czech Republic
ECCN	9N9999
ETIM 7	EC000228
Group Classification Key	P360
List of Characteristics	LV10.1
Metals Coefficient	LOA-----
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420
Unit of Measure	ST
Weight	4729 kg
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362090
Copper Weight	0
EAN	4042948830451
eClass 6	27-37-04-09
eClass 7.1	27-37-04-09
eClass 8	27-37-04-09
eClass Version 9	27-37-04-09
eClass Version 9.1	27-37-04-09
Quantity in Package	1
Packaging Length	265,00
Packaging Width	165,00
Packaging Height	170,00
Product Code	5374
Comparative Metals Coefficient	01.06.2012
Product Description	wyłącznik 3VA2 IEC Frame 630 zdolność załączania M Icu=55kA przy 415V 3-bieg., ochrona silnika, ETU350M, LSI, In=400A, zabezpieczenie od przeciążeń Ir=160A...400A zabezpieczenie przeciwzwarciowe Isd=3...15 x Ir, Ii=15 x In przyłącze płaskie śrubowe
UPC	804766431999

Article Number	3VA24405MN320AA0
Product Family	Ordering Data Overview
Product Group	5374
Catalog ID	LV10.1
Net Weight	10.426 lb
Packaging Dimensions	6.496 x 10.433 x 6.693
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Packaging Quantity	1 pieces
Commodity Code	85362090
Current Rating	400 A
Voltage Rating	690 V, 415 V
Number of Poles	3

Description

SIEMENS LOW VOLTAGE 3VA IEC MOTOR CIRCUIT PROTECTOR WITH ELECTRONIC TRIP UNIT. 3VA24 FRAME WITH MEDIUM (CLASS M) BREAKING CAPACITY. 400A 3-POLE Icu: (6KAIC AT 690V) (55KAIC AT 415V). ETU350M TRIP UNIT LSI. SPECIAL FEATURES: CONNECTION WITH LUG TERMINAL / NUT KEEPER. DIMENSIONS (W x H x D) IN: 5.4 x 9.8 x 5.4.