

### 3VA24507JP320AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3va24507jp320aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	3VA2450-7JP32-0AA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.04.2014
Configurable Product	False
Country of Origin	CZ
ECCN	9N9999
ETIM 7	EC000228
Group Classification Key	P360
List of Characteristics	LV10.1
Metals Coefficient	LOA-----
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362090
Copper Weight	0
EAN	4042948827321.0
eClass 6	27-37-04-09
eClass 7.1	27-37-04-09
eClass 8	27-37-04-09
eClass Version 9	27-37-04-09
eClass Version 9.1	27-37-04-09
Quantity in Package	1
Packaging Length	265,00
Packaging Width	165,00
Packaging Height	170,00
Product Code	5374
Comparative Metals Coefficient	01.04.2014
UPC	887621911362.0
Weight	4761
Article Number	3VA24507JP320AA0
Product Family	Ordering Data Overview
Catalog ID	LV10.1

<b>Packaging Dimensions</b>	6.496 x 10.433 x 6.693
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	690 V, 415 V
<b>Product Group</b>	5374
<b>Net Weight</b>	10.496 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85362090
<b>Current Rating</b>	500 A
<b>Number of Poles</b>	3

## Description

SIEMENS LOW VOLTAGE 3VA IEC MOLDED CASE CIRCUIT BREAKER WITH ELECTRONIC TRIP UNIT. 3VA24 FRAME WITH VERY HIGH (CLASS C) BREAKING CAPACITY. 500A 3-POLE Icu: (6KAIC AT 690V) (110KAIC AT 415V). ETU550 TRIP UNIT LCD LSI. SPECIAL FEATURES: CONNECTION WITH LUG TERMINAL / NUT KEEPER. DIMENSIONS (W x H x D) IN: 5.4 x 9.8 x 5.4.