

3VA24635HM320AA0

Industrial automation components

Manufacturer	Siemens
Catalog number	3va24635hm320aa0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	3VA2463-5HM32-0AA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.04.2014
Configurable Product	False
Country of Origin	Czech Republic
ECCN	9N9999
ETIM 7	EC000228
Group Classification Key	P360
List of Characteristics	LV10.1
Metals Coefficient	LOA-----
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420
Unit of Measure	ST
Quantity in Package	1
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362090
Copper Weight	0
EAN	4042948807682
eClass 6	27-37-04-09
eClass 7.1	27-37-04-09
eClass 8	27-37-04-09
eClass Version 9	27-37-04-09
eClass Version 9.1	27-37-04-09
Packaging Length	265,00
Packaging Width	165,00
Packaging Height	170,00
Product Code	5374
Comparative Metals Coefficient	01.04.2014
Weight	5186 kg
UPC	804766432392
Article Number	3VA24635HM320AA0
Product Family	Ordering Data Overview
Product Group	5374

Catalog ID	LV10.1
Net Weight	11.433 lb
Packaging Dimensions	6.496 x 10.433 x 6.693
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Packaging Quantity	1 pieces
Commodity Code	85362090
Current Rating	630 A
Voltage Rating	690 V, 415 V
Number of Poles	3

Description

SIEMENS LOW VOLTAGE 3VA IEC MOLDED CASE CIRCUIT BREAKER WITH ELECTRONIC TRIP UNIT. 3VA24 FRAME WITH MEDIUM (CLASS M) BREAKING CAPACITY. 630A 3-POLE Icu: (6KAIC AT 690V) (55KAIC AT 415V). ETU330 TRIP UNIT LIG. SPECIAL FEATURES: CONNECTION WITH LUG TERMINAL / NUT KEEPER. DIMENSIONS (W x H x D) IN: 5.4 x 9.8 x 5.4.