

3VA51106EC310AA0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 3va51106ec310aa0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|---|
| Product ID | 3VA5110-6EC31-0AA0 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.01.2016 |
| Configurable Product | False |
| Country of Origin | Czech Republic |
| ECCN | EAR99 |
| ETIM 7 | EC000228 |
| Group Classification Key | P360 |
| List of Characteristics | LV10 |
| Metals Coefficient | LOA----- |
| Packaging Size | MM |
| REACH | Lead CAS-Nr. 7439-92-1 |
| Unit of Measure | ST |
| Aluminium Weight | 0 |
| Argent Weight | 0 |
| Customs Tariff Code | 85362090 |
| Copper Weight | 0 |
| EAN | 4042948841280 |
| eClass 6 | 27-37-04-09 |
| eClass 7.1 | 27-37-04-09 |
| eClass 8 | 27-37-04-09 |
| eClass Version 9 | 27-37-04-09 |
| eClass Version 9.1 | 27-37-04-09 |
| Quantity in Package | 1 |
| Packaging Length | 150,00 |
| Packaging Width | 92,00 |
| Packaging Height | 116,00 |
| Product Code | 5385 |
| Comparative Metals Coefficient | 01.01.2016 |
| Weight | 960 kg |
| Product Description | wyłącznik 3VA5 UL Frame 125 zdolność załączania H 65kA przy 480V 3-bieg., ochrona instalacji TM230, FTAM, In=100A, zabezpieczenie od przeciążeń Ir=100A ustawione na stałe zabezpieczenie przeciwzwarciowe Ii=5...10 x In bez przyłącza |
| UPC | 804766300974 |
| Article Number | 3VA51106EC310AA0 |

| | |
|-------------------------------------|------------------------|
| Product Family | Ordering Data Overview |
| Product Group | 5385 |
| Catalog ID | LV10 |
| Net Weight | 2.123 lb |
| Packaging Dimensions | 3.622 x 5.906 x 4.567 |
| Package Size Unit of Measure | Inch |
| Quantity Unit | 1 Piece |
| Packaging Quantity | 1 pieces |
| Commodity Code | 85362090 |
| Current Rating | 100 A |
| Voltage Rating | 480 V |
| Number of Poles | 3 |

Description

SIEMENS LOW VOLTAGE 3VA UL MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT. 3VA51 FRAME WITH HIGH (CLASS H) BREAKING CAPACITY. 100A 3-POLE (25KAIC AT 600Y/347) (65KAIC AT 480V). TM230 TRIP UNIT WITH FIXED I_r ADJUSTABLE I_i . SPECIAL FEATURES: WITHOUT LUGS. DIMENSIONS (W x H x D) IN: 3 x 5.5 x 3.7.