

### 3VA52155ED310AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3va52155ed310aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

<b>Weight</b>	2.27 kgs
<b>Product ID</b>	3VA5215-5ED31-0AA0
<b>AL Field</b>	N
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85362090
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.01.2016
<b>Configurable Product</b>	False
<b>Copper Weight</b>	0
<b>Country of Origin</b>	CZ
<b>EAN</b>	4042948854259.0
<b>ECCN</b>	9N9999
<b>eClass 6</b>	27-37-04-09
<b>eClass 7.1</b>	27-37-04-09
<b>eClass 8</b>	27-37-04-09
<b>eClass Version 9</b>	27-37-04-09
<b>eClass Version 9.1</b>	27-37-04-09
<b>ETIM 7</b>	EC000228
<b>Group Classification Key</b>	P360
<b>List of Characteristics</b>	LV10
<b>Metals Coefficient</b>	L0A-----
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	245,00
<b>Packaging Width</b>	150,00
<b>Packaging Height</b>	160,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	wyłącznik 3VA5 UL Frame 250 zdolność załączania M 35kA przy 480V 3-bieg., ochrona instalacji TM210, FTFM, In=150A, zabezpieczenie od przeciążeń Ir=150A nastawiony na stałe zabezpieczenie przeciwzwarciowe Ii=10 x In bez przyłącza
<b>Product Code</b>	5385
<b>Comparative Metals Coefficient</b>	01.01.2016
<b>Unit of Measure</b>	ST
<b>UPC</b>	804766308505.0
<b>Catalog ID</b>	LV10
<b>Packaging Dimensions</b>	5.906 x 9.646 x 6.299

<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	600 V, 480 V
<b>Article Number</b>	3VA52155ED310AA0
<b>Product Family</b>	Ordering Data Overview
<b>Product Group</b>	5385
<b>Net Weight</b>	4.508 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	8536200020
<b>Current Rating</b>	150 A
<b>Number of Poles</b>	3

## Description

SIEMENS LOW VOLTAGE 3VA UL MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT. 3VA52 FRAME WITH MEDIUM (CLASS M) BREAKING CAPACITY. 150A 3-POLE (18KAIC AT 600V) (35KAIC AT 480V). TM210 TRIP UNIT WITH FIXED I<sub>r</sub> FIXED I<sub>i</sub>. SPECIAL FEATURES: WITHOUT LUGS. DIMENSIONS (W x H x D) IN: 4.1 x 7.3 x 4.2.