

### 3VA6110-5HN31-2AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3va6110-5hn31-2aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	2081
<b>Product ID</b>	3VA6110-5HN31-2AA0
<b>AL Field</b>	N
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85362090
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.01.2016
<b>Configurable Product</b>	False
<b>Copper Weight</b>	0
<b>Country of Origin</b>	CZ
<b>EAN</b>	4042948851562.0
<b>ECCN</b>	9N9999
<b>eClass 6</b>	27-37-04-09
<b>eClass 7.1</b>	27-37-04-09
<b>eClass 8</b>	27-37-04-09
<b>eClass Version 9</b>	27-37-04-09
<b>eClass Version 9.1</b>	27-37-04-09
<b>ETIM 7</b>	EC000228
<b>Group Classification Key</b>	P360
<b>List of Characteristics</b>	LV10
<b>Metals Coefficient</b>	L0A-----
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	242,00
<b>Packaging Width</b>	148,00
<b>Packaging Height</b>	159,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	wyłącznik 3VA6 UL rama 150 zdolność załączania M 35kA przy 480V 3-bieg., ochrona instalacji ETU350, LSI, In=100A, zabezpieczenie od przeciążeń 100% rated Ir=40A...100A zabezpieczenie przeciwzwarciowe Isd=1,5...10 x Ir, Ii=12 x In bez przyłącza
<b>Product Code</b>	5383
<b>Comparative Metals Coefficient</b>	01.01.2016
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420
<b>Unit of Measure</b>	ST
<b>UPC</b>	804766307065.0

<b>Article Number</b>	3VA61105HN312AA0
<b>Product Family</b>	Ordering Data Overview
<b>Catalog ID</b>	LV10
<b>Packaging Dimensions</b>	5.827 x 9.528 x 6.26
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	600 V, 480 V
<b>Product Group</b>	5383
<b>Net Weight</b>	4.588 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	8536200020
<b>Current Rating</b>	100 A
<b>Number of Poles</b>	3