

### 3VA9214-0RS20

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	3va9214-0rs20
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Product Description</b>	zabezpieczenie różnicowoprądowe RCD510 Basic RCD typ A zainstalowany z boku Znamionowy prąd uszkodzeniowy 0,03...5A przy 50/60Hz z regulacją tv 0...3000ms 4-bieg. In=250A Ue=127-480V akcesorium do: 3VA1 z przyłączem zaciskowym
<b>Product Code</b>	5376
<b>Comparative Metals Coefficient</b>	01.10.2014
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368
<b>Unit of Measure</b>	ST
<b>UPC</b>	804766449154.0
<b>Weight</b>	1516
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85363090
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.10.2014
<b>Configurable Product</b>	False
<b>Copper Weight</b>	0
<b>Country of Origin</b>	CN
<b>EAN</b>	4042949002277.0
<b>ECCN</b>	EAR99
<b>eClass 6</b>	27-37-92-01
<b>eClass 7.1</b>	27-37-92-01
<b>eClass 8</b>	27-37-92-01
<b>eClass Version 9</b>	27-37-92-01
<b>eClass Version 9.1</b>	27-37-92-01
<b>ETIM 7</b>	EC002498
<b>Group Classification Key</b>	P360
<b>List of Characteristics</b>	LV10.1
<b>Metals Coefficient</b>	L-A-----
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	230,00
<b>Packaging Width</b>	173,00
<b>Packaging Height</b>	117,00
<b>Packaging Size</b>	MM
<b>Product ID</b>	3VA9214-0RS20
<b>AL Field</b>	N
<b>Aluminium Weight</b>	0

<b>Article Number</b>	3VA92140RS20
<b>Product Family</b>	Ordering Data Overview
<b>Catalog ID</b>	LV10.1
<b>Packaging Dimensions</b>	6.811 x 9.055 x 4.606
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	480 V
<b>Frequency Range</b>	50 - 60 Hz
<b>Product Group</b>	5376
<b>Net Weight</b>	3.342 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85363090
<b>Current Rating</b>	250 A
<b>Number of Poles</b>	4
<b>Trip Curve</b>	Z