

3VA94240RL30

Industrial automation components

Manufacturer	Siemens
Catalog number	3va94240rl30
Category	Industrial automation components
Product type	Industrial automation components
Status	Legacy / discontinued

Technical specification

Product ID	3VA9424-0RL30
Compliance	Produkt zgodny z RoHS od: 01.04.2014
Configurable Product	False
Country of Origin	CN
ECCN	N
eClass 6	27-37-92-01
eClass 7.1	27-37-92-01
eClass 8	27-37-92-01
eClass Version 9	27-37-92-01
eClass Version 9.1	27-37-92-01
ETIM 7	EC002498
Group Classification Key	P360
List of Characteristics	LV10.1
Metals Coefficient	L-A-----
Packaging Length	207,00
Packaging Width	200,00
Packaging Height	164,00
Packaging Size	MM
Product Description	zabezpieczenie różnicowoprądowe RCD820 advanced RCD typ A zainstalowane na dole Znamionowy prąd uszkodzeniowy 0,03..30A przy 50/60Hz z regulacją tv 0...10000ms 4-bieg. In=630A, Ue=100-690V akcesorium do: 3VA2
Comparative Metals Coefficient	01.04.2014
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Diboron trioxide lblREACHCasNo3950
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85363090
Copper Weight	0
EAN	4042949002192.0
Quantity in Package	1
AL Field	N
Product Code	5376
UPC	804766449260.0
Weight	3641
Article Number	3VA94240RL30

Product Family	Ordering Data Overview
Catalog ID	LV10.1
Packaging Dimensions	7.874 x 8.15 x 6.457
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Frequency Range	50 - 60 Hz
Product Group	5376
Net Weight	7.886 lb
Packaging Quantity	1 pieces
Commodity Code	85363090
Current Rating	630 A
Voltage Rating	690 V
Number of Poles	4
Trip Curve	Z

Description

residual current device RCD820 advanced RCD type A load side mounted rated resid. current 0.03...30A at 50/60Hz adjustable tv 0...10000ms 4-pole In=630A Ue=100-690V accessory for: 3VA2