

4AV5135-2EB00-0A

Industrial automation components

Manufacturer	Siemens
Catalog number	4av5135-2eb00-0a
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

eClass 6	27-04-90-02
eClass 7.1	27-04-90-02
eClass 8	27-04-90-02
eClass Version 9	27-04-07-01
eClass Version 9.1	27-04-07-01
ETIM 7	EC002540
Product ID	4AV5135-2EB00-0A
AL Field	N
Product Description	ZASILACZ, 3-FAZ., PN(KW):0,84; U1N(V):400+/-20; U2N(V DC):24; I2(A DC):35; 50-60HZ, UKŁ.POŁ. /EKRANOW.UZW.:YY0 /0; KLASA OCHR.:I, TA/KL.IZOL.:40 /B; W(%):5; IP00; RODZAJ PRZYŁ.: ŚRUB. , INSTALLATION:4AV51_0_; EN 60742, EN61131
Comparative Metals Coefficient	01.07.2006
Unit of Measure	ST
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Copper Weight	3,180
Copper Weight Unit	KG
Country of Origin	CZ
Group Classification Key	R750
List of Characteristics	CC-IC10
Metals Coefficient	--3-----
Packaging Length	400,00
Packaging Width	380,00
Packaging Height	350,00
Packaging Size	MM
EAN	4001869931517.0
Quantity in Package	1
ECCN	N
Product Code	5877
Weight	15000
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85043180
Quantity Unit	1 Piece
Standards	EN 60742, EN61131-2

Article Number	4AV51352EB000A
Product Family	SIRIUS non-stabilized power supplies
Product Group	5877
Catalog ID	CC-IC10
Net Weight	31.967 lb
Packaging Dimensions	14.567 x 14.961 x 15.748
Package Size Unit of Measure	Inch
Packaging Quantity	1 pieces
Commodity Code	85043180
IP Rating	IP00
Fuse Characteristic	GR

Description

POWER SUPPLY; PHASES:3; PN(KW):0,84; UPRI(V):400+/-20; USEC(V DC):24; ISEC(A DC):35; F(HZ):50...60; VECTOR GR./SHIELD WNG.:YY0 /0; PROTECTION CL.:I; TA/ISOKL:40 /B; W(%):5; IP00; TYPE OF TERMINALS:SCREW CONNECTION; INSTALLATION:4AV51_0_; EN 60742, EN61131-2
>SAFETY ISOLATING TRANSFORMER<