

### 5SU1354-6KK10

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	5su1354-6kk10
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.12 kgs
eClass Version 9	27-14-22-07
eClass Version 9.1	27-14-22-07
ETIM 7	EC000905
List of Characteristics	LV10.1
Packaging Length	96,00
Packaging Width	40,00
Packaging Height	82,00
Packaging Size	MM
Product Description	WYŁĄCZNIK KOMBINOWANY FI/LS, TYP A, 30MA, 10KA, 1+N-BIEG., B10A
Comparative Metals Coefficient	01.06.2006
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368
Unit of Measure	ST
Customs Tariff Code	85362010
EAN	4001869307732.0
Quantity in Package	1
Product Code	5532
Product ID	5SU1354-6KK10
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.06.2006
Configurable Product	False
Country of Origin	R0
ECCN	N
eClass 6	27-14-22-07
eClass 7.1	27-14-22-07
eClass 8	27-14-22-07
Group Classification Key	P310

## Description

5SU1354-6KK10 | Siemens, Residual Circuit Breaker, 195 V ac, 10 A, 1 Pole, 20 kA, Type B, 35.4 x 76.2 x 90 mm | Brand / Manufacturer: Siemens | product type: Residual Circuit Breaker | type of actuator: Toggle | number of bars: 1 | rated voltage: 195 V ac | degree of strength: 20 kA (IEC 60947-2);10 kA (EN 60898) | current rating: 10 A | operating temperature range: -25 to +55 °C | trip type: Type B | connection type: Screw Terminal | type of attachment: DIN Rail Mount