

### 5SV3342-6KK12

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	5sv3342-6kk12
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Compliance</b>	Produkt zgodny z RoHS od: 01.06.2006
<b>Configurable Product</b>	False
<b>ECCN</b>	N
<b>eClass 6</b>	27-14-22-01
<b>eClass 7.1</b>	27-14-22-01
<b>eClass 8</b>	27-14-22-01
<b>eClass Version 9</b>	27-14-22-01
<b>eClass Version 9.1</b>	27-14-22-01
<b>ETIM 7</b>	EC000003
<b>Group Classification Key</b>	P310
<b>List of Characteristics</b>	LV10.1
<b>Metals Coefficient</b>	L-A-----
<b>Packaging Length</b>	78,00
<b>Packaging Width</b>	97,00
<b>Packaging Height</b>	85,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	wyłącznik ochronny różnicowy, 4-bieg., typ A, In: 25 A, 30 mA, Un AC: 400 V, SIGRES (trudne warunki otoczenia)
<b>Comparative Metals Coefficient</b>	01.06.2006
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105
<b>Unit of Measure</b>	ST
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85362010
<b>Copper Weight</b>	0
<b>EAN</b>	4001869430591.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	5511
<b>Weight</b>	374
<b>Product ID</b>	5SV3342-6KK12
<b>AL Field</b>	N
<b>Country of Origin</b>	DE