

### 5SV33424KK14

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	5sv33424kk14
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

Product ID	5SV3342-4KK14
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2018
Configurable Product	False
Country of Origin	DE
ECCN	9N9999
eClass 6	27-14-22-01
eClass 7.1	27-14-22-01
eClass 8	27-14-22-01
eClass Version 9	27-14-22-01
eClass Version 9.1	27-14-22-01
ETIM 7	EC000003
Group Classification Key	P310
List of Characteristics	LV10
Metals Coefficient	L-A-----
Packaging Length	78,00
Packaging Width	97,00
Packaging Height	85,00
Packaging Size	MM
Product Description	wyłącznik ochronny różnicowy, 4-bieg., typ B+, krótkozwłoczny, In: 25 A, 30 mA, Un AC: 400 V
Comparative Metals Coefficient	01.01.2018
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362010
Copper Weight	0
EAN	4001869549149.0
Quantity in Package	1
Product Code	5513
Weight	453
Article Number	5SV33424KK14
Product Family	Ordering Data Overview
Catalog ID	LV10

<b>Packaging Dimensions</b>	3.819 x 3.071 x 3.346
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating AC</b>	400 V
<b>Product Group</b>	5513
<b>Net Weight</b>	0.999 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85362010
<b>Current Rating</b>	25 A
<b>Number of Poles</b>	4
<b>Trip Curve</b>	D

## Description

Residual current operated circuit breaker, 4-pole, Type B+, short-time delayed, In: 25 A, 30 mA, Un AC: 400 V