

### 5SV3616-6KK01

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	5sv3616-6kk01
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	5SV3616-6KK01
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.06.2006
Configurable Product	False
Country of Origin	DE
ECCN	9N9999
ETIM 7	EC000003
Group Classification Key	P310
List of Characteristics	LV10.1
Metals Coefficient	L-A-----
Packaging Size	MM
Product Description	wyłącznik ochronny różnicowy, 2-bieg., typ A, krótkozwłoczny, In: 63 A, 300 mA, Un AC: 230 V
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105
Unit of Measure	ST
Packaging Width	97,00
Packaging Height	85,00
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362010
Copper Weight	0
EAN	4001869430850.0
eClass 6	27-14-22-01
eClass 7.1	27-14-22-01
eClass 8	27-14-22-01
eClass Version 9	27-14-22-01
eClass Version 9.1	27-14-22-01
Quantity in Package	1
Packaging Length	42,00
Product Code	5511
Comparative Metals Coefficient	01.06.2006
Weight	216 kg

## Description

Differential protective switch, 2-pole, type A, short delay, with rated current  $I_n$ : 63 A and sensitivity of 300 mA. Designed for operation at voltage  $U_n$  AC: 230 V. Product compliant with RoHS since 01.06.2006, manufactured in Germany. Weight is 216 g, and packaging dimensions are 42.00 mm in length, 97.00 mm in width, and 85.00 mm in height.