

### 5SV3646-6KK01

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	5sv3646-6kk01
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	5SV3646-6KK01
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.06.2006
Configurable Product	False
Country of Origin	DE
ECCN	N
ETIM 7	EC000003
Group Classification Key	P310
List of Characteristics	LV10.1
Metals Coefficient	L-A-----
Packaging Size	MM
Product Description	wyłącznik ochronny różnicowy, 4-bieg., typ A, krótkozwłoczny, In: 63 A, 300 mA, Un AC: 400 V
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one lblREACHCasNo8105
Unit of Measure	ST
Aluminium Weight	0
Argent Weight	0
Customs Tariff Code	85362010
Copper Weight	0
EAN	4001869430935.0
eClass 6	27-14-22-01
eClass 7.1	27-14-22-01
eClass 8	27-14-22-01
eClass Version 9	27-14-22-01
eClass Version 9.1	27-14-22-01
Quantity in Package	1
Packaging Length	78,00
Packaging Width	97,00
Packaging Height	85,00
Product Code	5511
Comparative Metals Coefficient	01.06.2006
Weight	376 kg

## Description

The differential protective switch is a 4-pole type A, short-time delay device with a rated current of 63 A and a sensitivity of 300 mA. Designed for use in AC 400 V installations, this product is RoHS compliant since June 1, 2006, and is manufactured in Germany. It weighs 376 g, with packaging dimensions of 78 mm in length, 97 mm in width, and 85 mm in height. The product is not configurable, and its customs tariff code is 85362010.