

### 6AG11366PA002BC0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag11366pa002bc0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Compliance</b>	Produkt zgodny z RoHS od: 08.08.2013
<b>Configurable Product</b>	False
<b>Product ID</b>	6AG1136-6PA00-2BC0
<b>AL Field</b>	N
<b>ECCN</b>	EAR99H
<b>ETIM 7</b>	EC002583
<b>Group Classification Key</b>	R151
<b>List of Characteristics</b>	A&DSE/SIP ADD
<b>Packaging Size</b>	CM
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
<b>Unit of Measure</b>	ST
<b>Customs Tariff Code</b>	85389091
<b>eClass 6</b>	27-24-26-11
<b>eClass 7.1</b>	27-24-26-11
<b>eClass 8</b>	27-24-26-11
<b>eClass Version 9</b>	27-24-26-11
<b>eClass Version 9.1</b>	27-24-26-11
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	7,70
<b>Packaging Width</b>	6,70
<b>Packaging Height</b>	2,40
<b>Product Code</b>	4257
<b>Comparative Metals Coefficient</b>	08.08.2013
<b>Weight</b>	84 kg
<b>Product Description</b>	SIPLUS ET 200SP -25...+60°C with conformal coating based on 6ES7136-6PA00-0BC0 . Power Module F-PM-E, PPM PROFIsafe, 24 V DC, safe shutdown of DQ and F-DQ up to PL D, SIL2 or PL E SIL3 2 for safe, dig. inputs, 1 for safe dig. output PPM
<b>EAN</b>	4047618053000
<b>Country of Origin</b>	Germany
<b>Article Number</b>	6AG11366PA002BC0
<b>Product Family</b>	SIPLUS special fail-safe modules
<b>Catalog ID</b>	A&DSE/SIP ADD
<b>Packaging Dimensions</b>	2.598 x 3.504 x 1.496
<b>Package Size Unit of Measure</b>	Inch

<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	24 V
<b>Product Group</b>	4257
<b>Net Weight</b>	0.218 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85389091

## Description

SIPLUS ET 200SP -25...+60°C with conformal coating based on 6ES7136-6PA00-0BC0 . Power Module F-PM-E, PPM PROFIsafe, 24 V DC, safe shutdown of DQ and F-DQ up to PL D, SIL2 or PL E SIL3 2 for safe, dig. inputs, 1 for safe dig. output PPM