

### 6AG1206-2BB00-7AC2

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag1206-2bb00-7ac2
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	6AG1206-2BB00-7AC2
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2003
Configurable Product	False
Country of Origin	DE
ECCN	5A991X
ETIM 7	EC000734
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Size	CM
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Weight	540 kg
Customs Tariff Code	85176200
EAN	4047618111236.0
eClass 6	19-17-01-06
eClass 7.1	19-17-01-06
eClass 8	19-17-01-06
eClass Version 9	19-17-01-06
eClass Version 9.1	19-17-01-06
Quantity in Package	1
Packaging Length	25,20
Packaging Width	19,30
Packaging Height	14,20
Product Code	4575
Comparative Metals Coefficient	01.01.2003

## Description

SIPLUS NET SCALANCE XC206-2 based on 6GK5206-2BB00-2AC2 with conformal coating, -40...+70 °C, manageable layer 2 IE switch; 6x 100 Mbps RJ45 ports; 2x 100 Mbps ST/BFOC ports; 1x console port; diagnostics LEDs redundant power supply temperature range -40 °C to +70 °C; assembly: DIN rail/S7 mounting rail/wall redundancy functions; office features (RSTP, VLAN,etc.); PROFINET IO device; Ethernet/IP-compliant C-Plug slot