

6AG1206-2BS00-7AC2

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 6ag1206-2bs00-7ac2 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--------------------------------------|
| Product ID | 6AG1206-2BS00-7AC2 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.01.2003 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | 5A991X |
| ETIM 7 | EC000734 |
| Group Classification Key | R151 |
| List of Characteristics | A&DSE/SIP ADD |
| Packaging Size | CM |
| REACH | Lead CAS-Nr. 7439-92-1 |
| Unit of Measure | ST |
| Weight | 540 |
| Customs Tariff Code | 85176200 |
| EAN | 4047618111502.0 |
| eClass 6 | 19-17-01-06 |
| eClass 7.1 | 19-17-01-06 |
| eClass 8 | 19-17-01-06 |
| eClass Version 9 | 19-17-01-06 |
| eClass Version 9.1 | 19-17-01-06 |
| Quantity in Package | 1 |
| Packaging Length | 25,20 |
| Packaging Width | 19,30 |
| Packaging Height | 14,20 |
| Product Code | 4575 |
| Comparative Metals Coefficient | 01.01.2003 |

Description

SIPLUS NET SCALANCE XC206-2SFP based on 6GK5206-2BS00-2AC2 with conformal coating, -40...+70 °C, manageable layer 2 IE switch 6x 10/100 Mbps RJ45 ports; 2x 100/1000 Mbps SFP 1x console port; diagnostics LEDs redundant power supply temperature range -40 °C to +70 °C; assembly: DIN rail/S7 mounting rail wall redundancy functions office features (RSTP, VLAN, etc.); PROFINET IO device; Ethernet/IP-compliant; C-Plug slot; C-PLUG slot