

## 6AG12111AE314XB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag12111ae314xb0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

### Technical specification

<b>Product Description</b>	SIPLUS S7-1200 CPU 1211C DC/DC/DC for medial exposure with conformal coating based on 6ES7211-1AE31-0XB0 . compact CPU, DC/DC/DC, onboard I/O: 6 DI 24 V DC 4 DO 24 V DC 2 AI 0-10 V DC, Power supply: 20.4-28.8V Program/data memory 30 KB
<b>EAN</b>	4047618042288
<b>Country of Origin</b>	Germany
<b>Article Number</b>	6AG12111AE314XB0
<b>Product Family</b>	SIPLUS CPU 1211C
<b>Product Group</b>	4578
<b>Catalog ID</b>	A&DSE/SIP ADD
<b>Net Weight</b>	0.816 lb
<b>Packaging Dimensions</b>	4.016 x 4.291 x 3.386
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85371091
<b>Voltage Rating</b>	24 V, 10 V, 28.8 V

### Description

The SIPLUS S7-1200 CPU 1211C DC/DC/DC is a compact CPU featuring onboard I/O: 6 DI 24 V DC, 4 DO 24 V DC, and 2 AI 0-10 V DC. It operates with a power supply of 20.4-28.8V and has a program/data memory of 30 KB. Designed for harsh environments, it includes a conformal coating. The net weight is 0.816 kg, and the packaging dimensions are 4.016 x 4.291 x 3.386 inches.