

### 6AG12141HF405XB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag12141hf405xb0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

Product ID	6AG1214-1HF40-5XB0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 19.12.2014
Configurable Product	False
Country of Origin	DE
ECCN	EAR99H
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Length	11,50
Packaging Width	11,00
Packaging Height	8,30
Packaging Size	CM
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Product Description	SIPLUS S7-1200 CPU 1214FC DC/DC/relay based on 6ES7214-1HF40-0XB0 with conformal coating, -25...+55 °C, compact CPU, DC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, power supply: DC 20.4-28.8 V DC, program/data memory 125 KB
Comparative Metals Coefficient	19.12.2014
Customs Tariff Code	85371091
EAN	4047618064716.0
Quantity in Package	1
Product Code	4578
Weight	399

## Description

SIPLUS S7-1200 CPU 1214FC DC/DC/relay -25...+55°C with conformal coating based on 6ES7214-1HF40-0XB0 . compact "CPU, DC/DC/relay, "onboard I/O:" "14 DI 24 V DC;" "10 DO relay 2" "A;" " 2 AI 0-10 V DC, Power" supply: DC 20.4-28.8 V DC Program/data memory 125 KB