

6AG1215-1AG40-5XB0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 6ag1215-1ag40-5xb0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| Weight | 0.45 kgs |
| Product ID | 6AG1215-1AG40-5XB0 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 12.12.2013 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | 5A991X |
| eClass 6 | 27-24-22-07 |
| eClass 7.1 | 27-24-22-07 |
| eClass 8 | 27-24-22-07 |
| eClass Version 9 | 27-24-22-07 |
| eClass Version 9.1 | 27-24-22-07 |
| ETIM 7 | EC000236 |
| Group Classification Key | R151 |
| List of Characteristics | A&DSE/SIP ADD |
| Packaging Length | 13,50 |
| Packaging Width | 11,50 |
| Packaging Height | 8,50 |
| Packaging Size | CM |
| Comparative Metals Coefficient | 12.12.2013 |
| REACH | Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7 |
| Unit of Measure | ST |
| Customs Tariff Code | 85371091 |
| EAN | 4047618055431.0 |
| Quantity in Package | 1 |
| Product Code | 4578 |

Description

SIPLUS S7-1200 CPU 1215C DC/DC/DC -40...+60°C with conformal coating based on 6ES7215-1AG40-0XB0 . compact CPU, DC/DC/DC, 2 PROFINET "ports, onboard I/O: ""14 DI 24 V" "DC; 10 DO 24 V DC;"" 2 AI 0-10 V" DC, 2 AO 0-20 mA DC, Power supply: DC 20.4-28.8V DC, Program/data memory 125 KB