

### 6AG1226-6RA32-5XB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag1226-6ra32-5xb0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

eClass 6	27-24-22-04
eClass 7.1	27-24-22-04
eClass 8	27-24-22-04
eClass Version 9	27-24-22-04
eClass Version 9.1	27-24-22-04
ETIM 7	EC001419
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Length	10,80
Packaging Width	8,50
Packaging Height	8,70
Packaging Size	CM
Product Description	SIPLUS S7-1200 SM 1226 F-DQ 2x relay based on 6ES7226-6RA32-0XB0 with conformal coating, -25...+55 °C, F-DQ 2x RLY 5A, PROFIsafe, 70 mm width, up to PL e (ISO 13849-1)/ SIL3 (IEC 61508)
Comparative Metals Coefficient	27.11.2014
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Product ID	6AG1226-6RA32-5XB0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 27.11.2014
Configurable Product	False
Country of Origin	DE
ECCN	EAR99H
Quantity in Package	1
Product Code	4578
Weight	345
Customs Tariff Code	85389091
EAN	4047618064730.0

## Description

SIPLUS S7-1200 SM 1226 F-DQ 2x relay -25...+55°C with conformal coating based on 6ES7226-6RA32-0XB0 . F-DQ 2x RLY 5A, PROFIsafe, 70 mm overall width, up to PL E (ISO 13849-1)/ SIL3 (IEC 61508)