

### 6AG12324HD322XB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag12324hd322xb0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Product ID</b>	6AG1232-4HD32-2XB0
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 15.03.2013
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	EAR99H
<b>ETIM 7</b>	EC001420
<b>Group Classification Key</b>	R151
<b>List of Characteristics</b>	A&DSE/SIP ADD
<b>Packaging Size</b>	CM
<b>Product Description</b>	SIPLUS S7-1200 SM 1232 based on 6ES7232-4HD32-0XB0 with conformal coating, -40...+70 °C, start up -25 °C, S7-1200, analog output, SM 1232, 4 AO, +/-10 V, 14-bit resolution, or 0-20 mA, 13-bit resolution
<b>REACH</b>	Lead CAS-Nr. 7439-92-1
<b>Unit of Measure</b>	ST
<b>Customs Tariff Code</b>	85389091
<b>EAN</b>	4047618051327.0
<b>eClass 6</b>	27-24-22-01
<b>eClass 7.1</b>	27-24-22-01
<b>eClass 8</b>	27-24-22-01
<b>eClass Version 9</b>	27-24-22-01
<b>eClass Version 9.1</b>	27-24-22-01
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	10,50
<b>Packaging Width</b>	8,80
<b>Packaging Height</b>	6,00
<b>Product Code</b>	4578
<b>Comparative Metals Coefficient</b>	15.03.2013
<b>Weight</b>	179 kg

## Description

SIPLUS S7-1200 SM 1232 -40...+70°C with conformal coating based on 6ES7232-4HD32-0XB0 . S7-1200, Analog output, SM 1232, 4 AO, +/-10 V, 14-bit resolution: or 0-20 mA, 13-bit resolution: