

6AG1315-2AH14-7AB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6ag1315-2ah14-7ab0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.16 kgs
Product ID	6AG1315-2AH14-7AB0
Notes	Wycofanie produktu od: 01.10.2023
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2012
Configurable Product	False
Country of Origin	DE
ECCN	EAR99H
eClass 6	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R151
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
List of Characteristics	A&DSE/SIP ADD
Packaging Length	13,00
Packaging Width	15,00
Packaging Height	5,00
Packaging Size	CM
Product Description	SIPLUS S7-300 CPU 315-2DP based on 6ES7315-2AH14-0AB0 with conformal coating, -25...+70 °C, central processing unit with MPI integrated power supply 24 V DC work memory 256 KB 2nd interface DP master/ slave Micro Memory Card required
Comparative Metals Coefficient	01.01.2012
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Customs Tariff Code	85371091
EAN	4042948510827.0
Quantity in Package	1
Product Code	4646

Description

6AG1315-2AH14-7AB0 | Siemens CPU Module, 24 Vdc with LAD, FBD, STL | Brand /
Manufacturer: Siemens | mass: 0.34 | product type: CPU Module | supply voltage: 24 V dc |
program capacity: 256 kB | power consumption: 850 mA | inrush current: 3.5 A | CPU
processing time: 0.05 μ s (Bit Operation) | for use with: Siplus S7 | number of digital
inputs: 16 | number of digital outputs: 16 | interface type: PROFIBUS;DP;MPI | a
programming language: LAD;FBD;STL | power loss: 4.5 W