

6AG1315-2EH14-7AB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6ag1315-2eh14-7ab0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.45 kgs
Compliance	Produkt zgodny z RoHS od: 01.01.2012
Product ID	6AG1315-2EH14-7AB0
Notes	Wycofanie produktu od: 01.10.2023
AL Field	N
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Length	13,00
Packaging Width	15,00
Packaging Height	4,80
Packaging Size	CM
Configurable Product	False
Country of Origin	DE
ECCN	N
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
Product Description	SIPLUS S7-300 CPU 315-2PN/DP based on 6ES7315-2EH14-0AB0 with conformal coating, -25...+70 °C, central processing unit with 384 KB work memory, 1st interface MPI/DP 12 Mbps, 2nd interface Ethernet PROFINET, with 2-port switch, Micro Memory Card required
Comparative Metals Coefficient	01.01.2012
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Customs Tariff Code	85371091
EAN	4042948538722.0
Quantity in Package	1
Product Code	4646

Description

6AG1315-2EH14-7AB0 | Siemens, CPU Module, 24 V dc, Capacity 384 KB (Integrated), 128 KB (Retentive) | Brand / Manufacturer: Siemens | mass: 0.45 | product type: CPU Module | supply voltage: 24 V dc | program capacity: 384 KB (Integrated);128 KB (Retentive) | power consumption: 750 mA | inrush current: 4 A | CPU processing time: 0.05 μ s (Bit Operations);0.09 μ s (Word Operations);0.12 μ s (Fixed Point Arithmetic);0.45 μ s (Floating Point Arithmetic) | interface type: MPI/DP 12MBIT/S;ETHERNET PROFINET WITH 2 PORT SWITCH;MICRO MEMORY CARD NECESSARY | a programming language: LAD;FBD;STL;SCL;GRAPH;HiGraph® | power loss: 4.65 W