

### 6AG1326-2BF41-2AB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag1326-2bf41-2ab0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.23 kgs
Product Description	SIPLUS S7-300 SM 326F DQ8 based on 6ES7326-2BF41-0AB0 with conformal coating, -25...+60 °C, digital output F-DQ 8x 24 V DC/2A PM fail-safe digital output sinking-sourcing up to category 4 (EN 954-1), SIL 3 (IEC 61508)
eClass Version 9.1	27-24-22-04
ETIM 7	EC001419
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Length	13,00
Packaging Width	15,00
Packaging Height	8,90
ECCN	EAR99H
eClass 6	27-24-22-04
eClass 7.1	27-24-22-04
eClass 8	27-24-22-04
eClass Version 9	27-24-22-04
Comparative Metals Coefficient	01.01.2012
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Product ID	6AG1326-2BF41-2AB0
Notes	Wycofanie produktu od: 01.10.2023
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2012
Configurable Product	False
Country of Origin	DE
Customs Tariff Code	85389091
EAN	4042948520406.0
Quantity in Package	1
Product Code	4646
Packaging Size	CM

## Description

SIPLUS S7-300 SM 326F DQ8 -25...+60°C with conformal coating based on 6ES7326-2BF41-0AB0 . Digital output F-DQ 8x 24 V DC/2A PM fail-safe digital output Sinking-sourcing up to Category 4 (EN 954-1), SIL 3 (IEC 61508)