

### 6AG14050KA027AA0

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6ag14050ka027aa0                 |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Product ID                     | 6AG1405-0KA02-7AA0  |
| AL Field                       | N   |
| Compliance                     | Produkt zgodny z RoHS od: 01.09.2014  |
| Configurable Product           | False   |
| Country of Origin              | DE  |
| ECCN                           | N   |
| ETIM 7                         | EC000599  |
| Group Classification Key       | R151  |
| List of Characteristics        | A&DSE/SIP ADD   |
| Packaging Size                 | CM  |
| Product Description            | SIPLUS S7-400 PS 405 10 A based on 6ES7405-0KA02-0AA0 with conformal coating, -25...+70 °C, power supply, wide range 10 A, 24/48/60 V DC; 5 V DC/10 A |
| REACH                          | Lead CAS-Nr. 7439-92-1  |
| Unit of Measure                | ST  |
| Weight                         | 1339 kg   |
| Customs Tariff Code            | 85044095  |
| EAN                            | 4042948599150.0   |
| eClass 6                       | 27-24-22-09   |
| eClass 7.1                     | 27-24-22-09   |
| eClass 8                       | 27-24-22-09   |
| eClass Version 9               | 27-24-22-09   |
| eClass Version 9.1             | 27-24-22-09   |
| Quantity in Package            | 1   |
| Packaging Length               | 30,00   |
| Packaging Width                | 23,00   |
| Packaging Height               | 6,00  |
| Product Code                   | 4656  |
| Comparative Metals Coefficient | 01.09.2014  |
| UPC                            | 887621217020.0  |

## Description

The SIPLUS S7-400 PS 405 10 A is a power supply based on 6ES7405-0KA02-0AA0, featuring a conformal coating and a temperature range of -25 to +70 °C. It offers a wide voltage range of 24/48/60 V DC and 5 V DC/10 A, with a maximum current of 10 A. The product is RoHS compliant since 01.09.2014 and is manufactured in Germany. It weighs 1.36 kg, with packaging dimensions of 30.00 x 23.00 x 6.00 cm.