

### 6AG1503-3CB00-2AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag1503-3cb00-2aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.45 kgs
<b>Product ID</b>	6AG1503-3CB00-2AA0
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.01.2012
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	EAR99H
<b>eClass 6</b>	19-17-01-90
<b>eClass 7.1</b>	19-17-01-14
<b>eClass 8</b>	19-17-01-14
<b>eClass Version 9</b>	19-17-01-14
<b>eClass Version 9.1</b>	19-17-01-14
<b>ETIM 7</b>	EC001467
<b>Group Classification Key</b>	R151
<b>List of Characteristics</b>	A&DSE/SIP ADD
<b>Packaging Length</b>	18,00
<b>Packaging Width</b>	14,20
<b>Packaging Height</b>	4,80
<b>Packaging Size</b>	CM
<b>Product Description</b>	SIPLUS NET OLM/G12 V4.0 based on 6GK1503-3CB00 with conformal coating, -25...+60 °C,
<b>Comparative Metals Coefficient</b>	01.01.2012
<b>REACH</b>	Lead CAS-Nr. 7439-92-1
<b>Unit of Measure</b>	ST
<b>Customs Tariff Code</b>	85176200
<b>EAN</b>	4042948427903.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	4575
<b>UPC</b>	40892549003.0

## Description

6AG1503-3CB00-2AA0 | Siemens, Communication Module, 24 V dc, 0.2 A, 9.6 kbit/s to 12 Mbit/s (PROFIBUS)/45.45 kbit/s (PROFIBUS PA), PROFIBUS/9-Pin Sub-D Socket, DIN Rail Mount/Wall Mount, 39.5 x 74.5 x 112 mm | Brand / Manufacturer: Siemens | height: 182 | product type: Communication Module | module type: Communication Module | supply voltage: 24 V dc | current rating: 0.2 A | data transfer indicator: 9.6 kbit/s to 12 Mbit/s (PROFIBUS);45.45 kbit/s (PROFIBUS PA) | interface type: PROFIBUS;9-Pin Sub-D Socket | type of attachment: DIN Rail Mount;Wall Mount | Size: 39.5 x 74.5 x 112 mm | minimum operating temperature: -25 °C | maximum working temperature: +70 °C | mass: 340 g | length: 39.5 mm | width: 74.5 mm | depth: 112 mm