

### 6AG15033CA012AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag15033ca012aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Product ID</b>	6AG1503-3CA01-2AA0
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.01.2012
<b>Configurable Product</b>	False
<b>Country of Origin</b>	Germany
<b>ECCN</b>	EAR99H
<b>ETIM 7</b>	EC001467
<b>Group Classification Key</b>	R151
<b>List of Characteristics</b>	A&DSE/SIP ADD
<b>Packaging Size</b>	CM
<b>REACH</b>	Lead CAS-Nr. 7439-92-1
<b>Unit of Measure</b>	ST
<b>Customs Tariff Code</b>	85176200
<b>eClass 6</b>	19-17-01-90
<b>eClass 7.1</b>	19-17-01-14
<b>eClass 8</b>	19-17-01-14
<b>eClass Version 9</b>	19-17-01-14
<b>eClass Version 9.1</b>	19-17-01-14
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	17,50
<b>Packaging Width</b>	14,00
<b>Packaging Height</b>	4,80
<b>Product Code</b>	4575
<b>Comparative Metals Coefficient</b>	01.01.2012
<b>Weight</b>	410 kg
<b>Product Description</b>	SIPLUS NET OLM/P12 V4.1 -25...+60°C start up temperature: -25°C with conformal coating based on 6GK1503-3CA01 . optical link module with 1 RS485 and 1 Plastic FOC interface (2 BFOC sockets), with signaling contact and test port
<b>EAN</b>	4047618072810
<b>Article Number</b>	6AG15033CA012AA0
<b>Product Family</b>	SIPLUS OLM optical link module
<b>Catalog ID</b>	A&DSE/SIP ADD
<b>Packaging Dimensions</b>	5.669 x 6.85 x 1.89
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece

<b>Product Group</b>	4575
<b>Net Weight</b>	1.102 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85176200

## Description

SIPLUS NET OLM/P12 V4.1 -25...+60°C start up temperature: -25°C with conformal coating based on 6GK1503-3CA01 . optical link module with 1 RS485 and 1 Plastic FOC interface (2 BFOC sockets), with signaling contact and test port