

### 6AG15225EH007AB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag15225eh007ab0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Product ID</b>	6AG1522-5EH00-7AB0
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 25.02.2013
<b>Configurable Product</b>	False
<b>Country of Origin</b>	Germany
<b>ECCN</b>	N
<b>ETIM 7</b>	EC001419
<b>Group Classification Key</b>	R151
<b>List of Characteristics</b>	A&DSE/SIP ADD
<b>Packaging Size</b>	CM
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
<b>Unit of Measure</b>	ST
<b>Customs Tariff Code</b>	85389091
<b>EAN</b>	4047618071417
<b>eClass 6</b>	27-24-22-04
<b>eClass 7.1</b>	27-24-22-04
<b>eClass 8</b>	27-24-22-04
<b>eClass Version 9</b>	27-24-22-04
<b>eClass Version 9.1</b>	27-24-22-04
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	15,00
<b>Packaging Width</b>	15,00
<b>Packaging Height</b>	4,00
<b>Product Code</b>	4657
<b>Comparative Metals Coefficient</b>	25.02.2013
<b>Weight</b>	342 kg
<b>Product Description</b>	SIPLUS S7-1500 DQ 16x48VUC/125V -40...+70°C with conformal coating based on "6ES7522-5EH00-0AB0 . "DQ16x" "24...48VUC/125V DC/0.5A; "16" "channels in groups of 1;" "0.5" "A per group;" "Substitute" "value;" "Observe derating"
<b>Article Number</b>	6AG15225EH007AB0
<b>Product Family</b>	SIPLUS SM 522 digital output modules
<b>Catalog ID</b>	A&DSE/SIP ADD
<b>Packaging Dimensions</b>	1.693 x 6.024 x 5.866
<b>Package Size Unit of Measure</b>	Inch

<b>Quantity Unit</b>	1 Piece
<b>Voltage Rating</b>	125 V
<b>Product Group</b>	4657
<b>Net Weight</b>	0.441 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85389091
<b>Current Rating</b>	0.5 A

## Description

The SIPLUS S7-1500 DQ 16x48VUC/125V is a digital output module featuring 16 channels in groups of 1, with a maximum current rating of 0.5 A per group. This product is RoHS compliant since February 25, 2013, and includes a conformal coating for reliability in harsh conditions, operating within a temperature range of -40 to +70 °C. It belongs to the SIPLUS SM 522 family and is packaged with dimensions of 1.693 x 6.024 x 5.866 inches. The net weight is 0.441 kg.