

### 6AG19613BA217AX0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag19613ba217ax0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	6AG1961-3BA21-7AX0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.08.2006
Configurable Product	False
Country of Origin	DE
ECCN	N
ETIM 7	EC002540
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Size	CM
Product Description	SIPLUS PS E202U redundancy module based on 6EP1961-3BA21 with conformal coating, -40...+70 °C, input/output: 24 V DC/40 A suitable for decoupling two SITOP power supplies with max. 20 A output current each
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Customs Tariff Code	85044095
EAN	4042948561638.0
eClass 6	27-04-90-02
eClass 7.1	27-04-90-02
eClass 8	27-04-90-02
eClass Version 9	27-04-07-01
eClass Version 9.1	27-04-07-01
Quantity in Package	1
Packaging Length	13,50
Packaging Width	15,00
Packaging Height	8,00
Product Code	4626
Comparative Metals Coefficient	01.08.2006
UPC	887621220518.0
Weight	482 kg

## Description

The SIPLUS PS E202U redundancy module based on 6EP1961-3BA21 features conformal coating, operating temperature range of -40...+70 °C, with input/output of 24 V DC/40 A, suitable for decoupling two SITOP power supplies with a maximum output current of 20 A each.