

6AG21366DB001CA0

Industrial automation components

Manufacturer	Siemens
Catalog number	6ag21366db001ca0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	6AG2136-6DB00-1CA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 08.08.2013
Configurable Product	False
Country of Origin	DE
ECCN	EAR99H
ETIM 7	EC001599
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Size	CM
Product Description	SIPLUS ET 200SP F-DQ 4x24VDC/2A PM rail based on 6ES7136-6DB00-0CA0 with conformal coating, -30...+60 °C, OT1 with ST1/2 (+70 °C für 10 minutes), fail-safe digital outputs up to PL e (ISO 13849), up to SIL 3 (IEC 61508)
Product Code	4C03
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Customs Tariff Code	85389091
EAN	4047618070045.0
eClass 6	27-24-26-04
eClass 7.1	27-24-26-04
eClass 8	27-24-26-04
eClass Version 9	27-24-26-04
eClass Version 9.1	27-24-26-04
Quantity in Package	1
Packaging Length	8,80
Packaging Width	6,50
Packaging Height	3,80
Comparative Metals Coefficient	08.08.2013
UPC	804766353253.0
Weight	76 kg

Description

The SIPLUS ET 200SP F-DQ 4x24VDC/2A PM is a rail-mounted product based on 6ES7136-6DB00-0CA0. It features highly reliable digital outputs, achieving PL e according to ISO 13849 and up to SIL 3 per IEC 61508. The device operates within a temperature range of -30 to +60 °C, with a short-term increase to +70 °C for 10 minutes. This product is RoHS compliant since 08.08.2013 and has REACH certifications. Packaging dimensions are 8.80 cm in length, 6.50 cm in width, and 3.80 cm in height, with a weight of 76 g.