

6AG22324HD321XB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6ag22324hd321xb0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	6AG2232-4HD32-1XB0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 15.03.2013
Configurable Product	False
Country of Origin	Germany
ECCN	EAR99H
ETIM 7	EC001420
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Size	CM
Product Code	4C02
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Customs Tariff Code	85389091
eClass 6	27-24-22-01
eClass 7.1	27-24-22-01
eClass 8	27-24-22-01
eClass Version 9	27-24-22-01
eClass Version 9.1	27-24-22-01
Quantity in Package	1
Packaging Length	10,60
Packaging Width	9,00
Packaging Height	5,60
Comparative Metals Coefficient	15.03.2013
UPC	195125335738.0
Weight	190 kg
Product Description	SIPLUS S7-1200 SM 1232 T1 RAIL -25 ... +55°C T1 with 70°C for 10 min with conformal coating based on 6ES7232-4HD32-0XB0. S7-1200, Analog output, SM 1232, 4 A0, +/-10 V, 14-bit resolution: or 0-20 mA, 13-bit resolution:
EAN	4047618073114
Article Number	6AG22324HD321XB0
Product Family	SIPLUS extreme S7-1200 SM 1232 RAIL
Product Group	4C02
Catalog ID	A&DSE/SIP ADD
Net Weight	0.472 lb

Packaging Dimensions	3.543 x 4.173 x 2.205
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Packaging Quantity	1 pieces
Commodity Code	85389091
Voltage Rating	10 V

Description

The SIPLUS S7-1200 SM 1232 T1 is a module based on 6ES7232-4HD32-0XB0, designed for harsh conditions with a conformal coating. It provides analog output with 14-bit resolution for +/-10 V signals and 13-bit resolution for 0-20 mA. Operating temperature ranges from -25 to +60 °C, with a short-term allowance up to +70 °C. The product is RoHS and REACH compliant, weighing 0.472 kg. Packaging dimensions are 3.543 x 4.173 x 2.205 inches.